



CS9000N SERIES

NEMA-3R Certified
"Sortie" Sign



Type:	_____
Project/Location:	_____
Contractor:	_____
Prepared By:	_____
Date:	_____
Model No.:	_____

TYPICAL SPECIFICATIONS

Supply and install **Ready-Lite® CS9000N Series** "SORTIE" Exit Signs. The equipment shall operate with universal two-wire AC input voltage from 120VAC to 347VAC at less than 1.5W and universal two-wire DC input voltage from 6VDC to 24VDC at less than 1.5W per face.

The sign housing shall be of grey fiberglass, specially designed for industrial environments. The sealed faceplate shall be gasketed, completely transparent, high abuse and vandal resistant, and will feature an even illuminated legend.

The light source illuminating the legend shall be **ALINGAP** technology red LEDs. The exit in a Self-Powered configuration shall include a magnetic test switch and a Nickel-Cadmium battery. The Exit Sign shall stay illuminated during emergency operation for at least 60 minutes upon AC failure.

The Exit Sign shall be CSA-C860 approved and meets CSA 22.2 No.141.

The equipment shall be **Ready-Lite®** Model: _____.

FEATURES

- Units are certified NEMA-3R
- Gasketed fiberglass housing designed specially for industrial applications
- Sealed, vandal-resistant clear polycarbonate faceplate
- Water, dust and oil resistant, suitable for high abuse areas, wet locations
- Long life, even illumination of the legend provided by energy-efficient **ALINGAP** technology LED light source consuming less than 3W per face
- Wall, ceiling or end mount.
- Mounting bracket available for ease of installation
- Normal AC and emergency DC operation – 120V to 347VAC and 6V to 24VDC input
- CSA certified, meets or exceeds CSA 22.2 No. 141 requirements

WIRE GUARDS

460.0081-RL	wall mount
460.0104-RL	ceiling mount
460.0124-RL	end mount

DIMENSIONS

Dimensions are approximate and subject to change.



POWER CONSUMPTION AND UNIT RATING

MODEL	AC SPECS		DC SPECS	
AC/DC standard	120 to 347VAC	less than 1.5W	6 to 24VDC	less than 1.5W
AC/special DC	120/277/ 347VAC	less than 2.5W	36 or 48 or 120VDC	less than 2.5W
Self-Powered	120 to 347VAC	less than 3W	nickel-cadmium battery	minimum 60 minutes

Note: double face models have double the power consumption above.

ORDERING INFORMATION

SERIES	VOLTAGE
<p>CS9100N= sortie, single face, wall, end and ceiling mount</p> <p>CS9200N= sortie, double face, end or ceiling mount</p>	<p>UL= 120/277/347VAC, 6/12/24VDC</p> <p>LI2012W= 120VAC, 120VDC 2 wires</p> <p>LU36= 120/277/347VAC - 36VDC 4 wires</p> <p>LU48= 120/277/347VAC - 48VDC 4 wires</p> <p>LU120= 120/277/347VAC - 120VDC 4 wires</p> <p>ISP= Self-Powered, 120 to 347VAC</p>

EXAMPLE: CS9100NUL

Special wording available. see page 87. Please consult your sales representative.