

# FINISHES

ExpressTray® is offered in three material and finish combinations:

### ELECTRO-GALVANIZED STEEL

By means of an electrolysis process after fabrication, a zinc coating is bonded to the surface of the steel tray. The electro-galvanized zinc coating is ideally suited for indoor applications.

### HOT-DIPPED GALVANIZED STEEL

The zinc coating is provided by immersing the product in a molten zinc bath. This finish is ideal for outdoor installations exposed to corrosion accelerators such as pollution, sea air and other mild atmospheric conditions, and can also be used for indoor applications requiring additional corrosion resistance.

### STAINLESS STEEL (TYPES 304 and 316)

Stainless steel with no additional surface treatment provides the highest protection against corrosion and is used primarily in marine environments, food processing and other industrial facilities, both indoor and outdoor.

## 2" DEEP U-PROFILE - Maximum Suggested Load

Width in. (mm)	QuikLok™ "ETQ" Series				Wire Size in. (mm)	Span											
	Electro-Galvanized	Hot-Dipped Galvanized	Stainless Steel (304)	Stainless Steel (316)		5 ft/1.5 m		6 ft/1.75 m		7 ft/2 m		8ft/2.5 m		9 ft/2.75 m		10 ft/3 m	
	lb/ft	kg/m	lb/ft	kg/m		lb/ft	kg/m	lb/ft	kg/m	lb/ft	kg/m	lb/ft	kg/m	lb/ft	kg/m	lb/ft	kg/m
4 (100)	<b>ETQ 2004SE10</b>	<b>ETQ 2004SH10</b>	<b>ETQ 2004SS10</b>	<b>ETQ 2004S610</b>	.153 (3.9)	32	48	22	33	16	24	13	19	10	15	8	12
6 (150)	<b>ETQ 2006SE10</b>	<b>ETQ 2006SH10</b>	<b>ETQ 2006SS10</b>	<b>ETQ 2006S610</b>	.153 (3.9)	36	54	25	37	18	27	14	21	11	17	9	13
8 (200)	<b>ETQ 2008SE10</b>	<b>ETQ 2008SH10</b>	<b>ETQ 2008SS10</b>	<b>ETQ 2008S610</b>	.153 (3.9)	36	54	25	37	18	27	14	21	11	17	9	13
12 (300)	<b>ETQ 2012SE10</b>	<b>ETQ 2012SH10</b>	<b>ETQ 2012SS10</b>	<b>ETQ 2012S610</b>	.189 (4.8)	72	107	50	75	37	55	28	42	22	33	18	27
16 (400)	<b>ETQ 2016SE10</b>	<b>ETQ 2016SH10</b>	<b>ETQ 2016SS10</b>	<b>ETQ 2016S610</b>	.189 (4.8)	72	107	50	75	37	55	28	42	22	33	18	27
18 (450)	<b>ETQ 2018SE10</b>	<b>ETQ 2018SH10</b>	<b>ETQ 2018SS10</b>	<b>ETQ 2018S610</b>	.189 (4.8)	72	107	50	75	37	55	28	42	22	33	18	27
20 (500)	<b>ETQ 2020SE10</b>	<b>ETQ 2020SH10</b>	<b>ETQ 2020SS10</b>	<b>ETQ 2020S610</b>	.189 (4.8)	72	107	50	75	37	55	28	42	22	33	18	27
24 (600)	<b>ETQ 2024SE10</b>	<b>ETQ 2024SH10</b>	<b>ETQ 2024SS10</b>	<b>ETQ 2024S610</b>	.189 (4.8)	88	131	61	91	45	67	34	51	27	41	22	33

Width in. (mm)	"ETU" Series				Wire Size in. (mm)	Span											
	Electro-Galvanized	Hot-Dipped Galvanized	Stainless Steel (304)	Stainless Steel (316)		5 ft/1.5 m		6 ft/1.75 m		7 ft/2 m		8ft/2.5 m		9 ft/2.75 m		10 ft/3 m	
	lb/ft	kg/m	lb/ft	kg/m		lb/ft	kg/m	lb/ft	kg/m	lb/ft	kg/m	lb/ft	kg/m	lb/ft	kg/m	lb/ft	kg/m
2 (50)	<b>ETU 2002SE10</b>	<b>ETU 2002SH10</b>	<b>ETU 2002SS10</b>	<b>ETU 2002S610</b>	.153 (3.9)	20	30	14	21	10	15	8	12	6	9	5	7
4 (100)	<b>ETU 2004SE10</b>	<b>ETU 2004SH10</b>	<b>ETU 2004SS10</b>	<b>ETU 2004S610</b>	.153 (3.9)	32	48	22	33	16	24	13	19	10	15	8	12
6 (150)	<b>ETU 2006SE10</b>	<b>ETU 2006SH10</b>	<b>ETU 2006SS10</b>	<b>ETU 2006S610</b>	.153 (3.9)	36	54	25	37	18	27	14	21	11	17	9	13
8 (200)	<b>ETU 2008SE10</b>	<b>ETU 2008SH10</b>	<b>ETU 2008SS10</b>	<b>ETU 2008S610</b>	.173 (4.4)	48	72	33	50	24	37	19	28	15	22	12	18
12 (300)	<b>ETU 2012SE10</b>	<b>ETU 2012SH10</b>	<b>ETU 2012SS10</b>	<b>ETU 2012S610</b>	.173 (4.4)	64	95	44	66	33	49	25	37	20	29	16	24
16 (400)	<b>ETU 2016SE10</b>	<b>ETU 2016SH10</b>	<b>ETU 2016SS10</b>	<b>ETU 2016S610</b>	.189 (4.8)	72	107	50	75	37	55	28	42	22	33	18	27
18 (450)	<b>ETU 2018SE10</b>	<b>ETU 2018SH10</b>	<b>ETU 2018SS10</b>	<b>ETU 2018S610</b>	.189 (4.8)	72	107	50	75	37	55	28	42	22	33	18	27
20 (500)	<b>ETU 2020SE10</b>	<b>ETU 2020SH10</b>	<b>ETU 2020SS10</b>	<b>ETU 2020S610</b>	.189 (4.8)	88	131	61	91	45	67	34	51	27	41	22	33
24 (600)	<b>ETU 2024SE10</b>	<b>ETU 2024SH10</b>	<b>ETU 2024SS10</b>	<b>ETU 2024S610</b>	.189 (4.8)	88	131	61	91	45	67	34	51	27	41	22	33

## 4" DEEP U-PROFILE - Maximum Suggested Load

Width in. (mm)	QuikLok™ "ETQ" Series				Wire Size in. (mm)	Span											
	Electro- Galvanized	Hot-Dipped Galvanized	Stainless Steel (304)	Stainless Steel (316)		5 ft/1.5 m		6 ft/1.75 m		7 ft/2 m		8ft/2.5 m		9 ft/2.75 m		10 ft/3 m	
	lb/ft	kg/m	lb/ft	kg/m		lb/ft	kg/m	lb/ft	kg/m	lb/ft	kg/m	lb/ft	kg/m	lb/ft	kg/m	lb/ft	kg/m
4 (100)	<b>ETQ 4004SE10</b>	<b>ETQ 4004SH10</b>	<b>ETQ 4004SS10</b>	<b>ETQ 4004S610</b>	.153 (3.9)	32	48	22	33	16	24	13	19	10	15	8	12
6 (150)	<b>ETQ 4006SE10</b>	<b>ETQ 4006SH10</b>	<b>ETQ 4006SS10</b>	<b>ETQ 4006S610</b>	.153 (3.9)	36	54	25	37	18	27	14	21	11	17	9	13
8 (200)	<b>ETQ 4008SE10</b>	<b>ETQ 4008SH10</b>	<b>ETQ 4008SS10</b>	<b>ETQ 4008S610</b>	.189 (4.8)	72	107	50	75	37	55	28	42	22	33	18	27
12 (300)	<b>ETQ 4012SE10</b>	<b>ETQ 4012SH10</b>	<b>ETQ 4012SS10</b>	<b>ETQ 4012S610</b>	.189 (4.8)	96	143	67	99	49	73	38	56	30	44	24	36
16 (400)	<b>ETQ 4016SE10</b>	<b>ETQ 4016SH10</b>	<b>ETQ 4016SS10</b>	<b>ETQ 4016S610</b>	.189 (4.8)	96	143	67	99	49	73	38	56	30	44	24	36
18 (450)	<b>ETQ 4018SE10</b>	<b>ETQ 4018SH10</b>	<b>ETQ 4018SS10</b>	<b>ETQ 4018S610</b>	.189 (4.8)	96	143	67	99	49	73	38	56	30	44	24	36
20 (500)	<b>ETQ 4020SE10</b>	<b>ETQ 4020SH10</b>	<b>ETQ 4020SS10</b>	<b>ETQ 4020S610</b>	.189 (4.8)	104	155	72	108	53	79	41	61	32	48	26	39
24 (600)	<b>ETQ 4024SE10</b>	<b>ETQ 4024SH10</b>	<b>ETQ 4024SS10</b>	<b>ETQ 4024S610</b>	.189 (4.8)	108	161	75	112	55	82	42	63	33	50	27	40

Width in. (mm)	"ETU" Series				Wire Size in. (mm)	Span											
	Electro- Galvanized	Hot-Dipped Galvanized	Stainless Steel (304)	Stainless Steel (316)		5 ft/1.5 m		6 ft/1.75 m		7 ft/2 m		8ft/2.5 m		9 ft/2.75 m		10 ft/3 m	
	lb/ft	kg/m	lb/ft	kg/m		lb/ft	kg/m	lb/ft	kg/m	lb/ft	kg/m	lb/ft	kg/m	lb/ft	kg/m	lb/ft	kg/m
4 (100)	<b>ETU 4004SE10</b>	<b>ETU 4004SH10</b>	<b>ETU 4004SS10</b>	<b>ETU 4004S610</b>	.153 (3.9)	32	48	22	33	16	24	13	19	10	15	8	12
6 (150)	<b>ETU 4006SE10</b>	<b>ETU 4006SH10</b>	<b>ETU 4006SS10</b>	<b>ETU 4006S610</b>	.153 (3.9)	36	54	25	37	18	27	14	21	11	17	9	13
8 (200)	<b>ETU 4008SE10</b>	<b>ETU 4008SH10</b>	<b>ETU 4008SS10</b>	<b>ETU 4008S610</b>	.173 (4.4)	72	107	50	75	37	55	28	42	22	33	18	27
12 (300)	<b>ETU 4012SE10</b>	<b>ETU 4012SH10</b>	<b>ETU 4012SS10</b>	<b>ETU 4012S610</b>	.189 (4.8)	96	143	67	99	49	73	38	56	30	44	24	36
16 (400)	<b>ETU 4016SE10</b>	<b>ETU 4016SH10</b>	<b>ETU 4016SS10</b>	<b>ETU 4016S610</b>	.189 (4.8)	96	143	67	99	49	73	38	56	30	44	24	36
18 (450)	<b>ETU 4018SE10</b>	<b>ETU 4018SH10</b>	<b>ETU 4018SS10</b>	<b>ETU 4018S610</b>	.189 (4.8)	96	143	67	99	49	73	38	56	30	44	24	36
20 (500)	<b>ETU 4020SE10</b>	<b>ETU 4020SH10</b>	<b>ETU 4020SS10</b>	<b>ETU 4020S610</b>	.189 (4.8)	104	155	72	108	53	79	41	61	32	48	26	39
24 (600)	<b>ETU 4024SE10</b>	<b>ETU 4024SH10</b>	<b>ETU 4024SS10</b>	<b>ETU 4024S610</b>	.189 (4.8)	108	161	75	112	55	82	42	63	33	50	27	40



## 6" DEEP U-PROFILE - Maximum Suggested Load

Width in. (mm)	Electro- Galvanized	Hot-Dipped Galvanized	Wire Size in. (mm)	Span											
				5 ft/1.5 m		6 ft/1.75 m		7 ft/2 m		8ft/2.5 m		9 ft/2.75 m		10 ft/3 m	
				lb/ft	kg/m	lb/ft	kg/m	lb/ft	kg/m	lb/ft	kg/m	lb/ft	kg/m	lb/ft	kg/m
12 (300)	<b>ETU 6012SE10</b>	<b>ETU 6012SH10</b>	.250 (6.4)	-	-	173	259	127	190	97	145	77	115	65	97
18 (450)	<b>ETU 6018SE10</b>	<b>ETU 6018SH10</b>	.250 (6.4)	-	-	173	259	127	190	97	145	77	115	65	97
20 (500)	<b>ETU 6020SE10</b>	<b>ETU 6020SH10</b>	.250 (6.4)	-	-	173	259	127	190	97	145	77	115	65	97
24 (600)	<b>ETU 6024SE10</b>	<b>ETU 6024SH10</b>	.250 (6.4)	-	-	173	259	127	190	97	145	77	115	65	97

## 2-1/2" DEEP U-PROFILE - Maximum Suggested Load

Width in. (mm)	"ETC" Series				Wire Size in. (mm)	Span											
	Electro- Galvanized	Hot-Dipped Galvanized	Stainless Steel (304)	Stainless Steel (316)		5 ft/1.5 m		6 ft/1.75 m		7 ft/2 m		8ft/2.5 m		9 ft/2.75 m		10 ft/3 m	
	lb/ft	kg/m	lb/ft	kg/m		lb/ft	kg/m	lb/ft	kg/m	lb/ft	kg/m	lb/ft	kg/m	lb/ft	kg/m	lb/ft	kg/m
2 (50)	—	<b>ETC 2502SH10</b>	<b>ETC 2502SS10</b>	—	.177 (4.5)	36.1	53.7	25.1	37.4	18.4	27.4	14.1	21.0	11.0	16.4	9.8	14.6
4 (100)	—	<b>ETC 2504SH10</b>	<b>ETC 2504SS10</b>	—	.177 (4.5)	65.8	97.9	45.7	68.0	33.6	50.0	25.7	38.2	15.0	22.3	12.8	19.0
8 (200)	—	<b>ETC 2508SH10</b>	<b>ETC 2508SS10</b>	—	.177 (4.5)	67.1	99.9	46.6	69.3	34.2	50.9	26.2	39.0	20.0	29.8	16.7	24.9
12 (300)	—	<b>ETC 2512SH10</b>	—	—	.177 (4.5)	95.5	142.1	66.3	98.7	48.7	72.5	37.3	55.5	22.6	33.6	18.7	27.8
16 (400)	—	<b>ETC 2516SH10</b>	—	—	.177 (4.5)	82.4	122.6	57.2	85.1	42.1	62.7	32.2	47.9	22.3	33.2	18.2	27.1