



Fork terminals with nylon insulation sleeves, recommended for temperatures up to 105°C. Inner bronze insulation grip sleeve lengthens flex radius of conductor and eliminates conductor creep. Nylon jacket is colour-coded.

Stock thickness same as ring terminal of same size.


Most standard bulk catalogue numbers can be put on Mylar Tape for reel fed applications (i.e. 12050 tool and application dies). See pages 196-197. Please put the suffix M for Mylar Tape RA2573M. (Bulk number 1000 and 500 packages.)

Nylon Insulated Fork – Insulation Grip

Cat. No.	Pkg. Qty.	Wire Range	Max. Ins.	Bolt Hole	Wt./lb. Per 1000	Dimensions			
						A	B	C	M
RA18-6F	100	22-16	.136	#6	3	.83	.25	.25	.71
RA1103	1000	22-16	.136	#6	3	.83	.25	.25	.71
RA18-8F	100	22-16	.136	#8	3	.86	.31	.25	.71
RA1123	1000	22-16	.136	#8	3	.86	.31	.25	.71
RA18-10F	100	22-16	.136	#10	3	.86	.31	.25	.71
RA1153	1000	22-16	.136	#10	3	.86	.31	.25	.71
RA18-14F	100	22-16	.136	1/4"	4	.95	.44	.31	.70
RA1163	1000	22-16	.136	1/4"	4	.95	.44	.31	.70
RB14-6F	100	18-14	.162	#6	3-1/2	.87	.31	.25	.71
RB1113	1000	18-14	.162	#6	3-1/2	.87	.31	.25	.71
RB14-8F	100	18-14	.162	#8	3-1/2	.87	.31	.25	.71
RB1123	1000	18-14	.162	#8	3-1/2	.87	.31	.25	.71
RB14-10F	100	18-14	.162	#10	4	.87	.38	.25	.71
RB1153	1000	18-14	.162	#10	4	.87	.38	.25	.71
RB14-14F	100	18-14	.162	1/4"	4	.95	.44	.28	.74
RB1163	1000	18-14	.162	1/4"	4	.95	.44	.28	.74
RB1103	1000	18-14	.162	#6	6	.74	.28	.16	.60
RB1124	1000	18-14	.190	#8	6	.95	.31	.25	.79
RB1154	1000	18-14	.190	#10	6	.95	.31	.25	.79
RC10-6F	50	12-10	.210	#6	6	.97	.31	.27	.81
RC1113	500	12-10	.210	#6	6	.97	.31	.27	.81
RC10-8F	50	12-10	.210	#8	6	1.00	.37	.27	.81
RC1123	500	12-10	.210	#8	6	1.00	.37	.27	.81
RC10-10F	50	12-10	.210	#10	6	1.00	.37	.27	.81
RC1153	500	12-10	.210	#10	6	1.00	.37	.27	.81
RC10-14F	50	12-10	.210	1/4"	6	1.12	.50	.27	.86
RC1163	500	12-10	.210	1/4"	6	1.12	.50	.27	.86
RC1124	500	12-10	.250	#8	6	1.10	.37	.27	.91
RC1154	500	12-10	.250	#10	6	1.10	.37	.27	.91

U.L. Listed E9809

Installing tools: WT145C, WT2000, WT112M, ERG4001, ERG2003, WT145A





Fork terminals allow easy installation because screw needs only to be loosened. Suffix S indicates a flanged-tongue fork with turned up tips for extra holding protection.

Stock thickness same as ring terminal of same size.

Most standard bulk catalogue numbers can be put on Mylar Tape for reel fed applications (i.e. 12050 tool and application dies).

See pages 196-197.


Please put the suffix M for Mylar Tape RA2573M. (Bulk number 1000 and 500 packages.)

Nylon Insulated Fork Flanged Tongue – Insulation Grip

Cat. No.	Pkg. Qty.	Wire Range	Max. Ins.	Bolt Hole	Wt./lb. Per 1000	Dimensions			
						A	B	C	M
RA18-6FS	100	22-16	.136	#6	3	.75	.28	.16	.62
RA1203	1000	22-16	.136	#6	3	.75	.28	.16	.62
RA18-8FS	100	22-16	.136	#8	3	.89	.31	.23	.65
RA1223	1000	22-16	.136	#8	3	.89	.31	.23	.65
RA18-10FS	100	22-16	.136	#10	3	.93	.38	.26	.68
RA1253	1000	22-16	.136	#10	3	.93	.38	.26	.68
RB14-6FS	100	18-14	.162	#6	4	.74	.28	.16	.60
RB1203	1000	18-14	.162	#6	4	.74	.28	.16	.60
RB14-8FS	100	18-14	.162	#8	4	.89	.31	.23	.66
RB1223	1000	18-14	.162	#8	4	.89	.31	.23	.66
RB14-10FS	100	18-14	.162	#10	4	.94	.38	.27	.69
RB1253	1000	18-14	.162	#10	4	.94	.38	.27	.69
RB1204	1000	18-14	.190	#6	4	.79	.28	.16	.67
RB1224	1000	18-14	.190	#8	4	.94	.31	.23	.71
RC10-8FS	50	12-10	.210	#8	5	.97	.34	.23	.73
RC1223	500	12-10	.210	#8	5	.97	.34	.23	.73
RC10-10FS	50	12-10	.210	#10	5	1.00	.38	.26	.74
RC1253	500	12-10	.210	#10	5	1.00	.38	.26	.74
RC1224	1000	12-10	.250	#8	5	1.08	.34	.23	.80
RC1254	1000	12-10	.250	#10	5	1.12	.38	.26	.86

U.L. Listed E9809

Installing tools: WT145C, WT2000, WT112M, ERG4001, ERG2003, WT145A, WT2130A(RC)



Sta-Kon®

Terminals



These fork terminals have extra-long PVC insulation sleeve for protection and stress relief at wire's flex point. Brazed seam barrel is serrated for high pull-out value. Terminal is high conductivity electrolytic copper, electro-tin plated. Insulation is colour-coded.


Stock thickness same as ring terminal of same size.

Most standard bulk catalogue numbers can be put on Mylar Tape for reel fed applications (i.e. 12050 tool and application dies). See pages 196-197. Please put the suffix M for Mylar Tape RA2573M. (Bulk number 1000 and 500 packages.)

Vinyl Insulated Fork – Insulation Support

Cat. No.	Pkg. Qty.	Wire Range	Max. Ins.	Bolt Hole	Wt./lb. Per 1000	Dimensions			
						A	B	C	M
18RA-6F	100	22-16	.150	#6	5	.94	.25	.27	.81
RA1167	1000	22-16	.150	#6	5	.94	.25	.27	.81
18RA-8F	100	22-16	.150	#8	5	.97	.31	.27	.81
RA1147	1000	22-16	.150	#8	5	.97	.31	.27	.81
18RA-10F	100	22-16	.150	#10	5	.97	.31	.27	.81
RA1157	1000	22-16	.150	#10	5	.97	.31	.27	.81
14RB-6F	100	18-14	.170	#6	6	.97	.31	.27	.81
RB647	1000	18-14	.170	#6	6	.97	.31	.27	.81
14RB-6FS	100	18-14	.170	#6	6	.89	.30	.25	.75
14RB-8F	100	18-14	.170	#8	6	.97	.31	.27	.81
RB657	1000	18-14	.170	#8	6	.97	.31	.27	.81
14RB-10F	100	18-14	.170	#10	6	.97	.31	.27	.81
RB1157	1000	18-14	.170	#10	6	.97	.31	.27	.81
14RB-14F	100	18-14	.170	1/4"	6	1.11	.44	.38	.89
RB1717	1000	18-14	.170	1/4"	6	1.11	.44	.38	.89
10RC-6F	50	12-10	.210	#6	7	1.09	.38	.27	.90
RC1337	500	12-10	.210	#6	7	1.09	.38	.27	.90
10RC-8F	50	12-10	.210	#8	7	1.09	.38	.27	.90
RC1147	500	12-10	.210	#8	7	1.09	.38	.27	.90
10RC-10F	50	12-10	.210	#10	7	1.09	.38	.27	.90
RC1157	500	12-10	.210	#10	7	1.09	.38	.27	.90
10RC-14F	50	12-10	.210	1/4"	7	1.15	.50	.37	.90
RC1167	500	12-10	.210	1/4"	7	1.15	.50	.37	.90


U.L. Listed E9809. Installing tools: WT145C, WT2000, WT112M, ERG4001, ERG2003, WT2130A(RC)



Vinyl Insulation Fork – Expanded Insulation Support

Cat. No.	Pkg. Qty.	Wire Range	Max. Ins.	Bolt Hole	Wt./lb. Per 1000	Dimensions			
						A	B	C	M
18RA-6FX	100	22-16	.170	#6	5	.94	.25	.27	.81
RA1167-170	1000	22-16	.170	#6	5	.94	.25	.27	.81
18RA-8FX	100	22-16	.170	#8	5	.97	.31	.27	.81
RA1147-170	1000	22-16	.170	#8	5	.97	.31	.27	.81
18RA-10FX	100	22-16	.170	#10	5	.97	.31	.27	.81
RA1157-170	1000	22-16	.170	#10	5	.97	.31	.27	.81
14RB-6FX	100	18-14	.200	#6	6	.97	.31	.27	.81
RB647-200	1000	18-14	.200	#6	6	.97	.31	.27	.81
14RB-8FX	100	18-14	.200	#8	6	.97	.31	.27	.81
RB657-200	1000	18-14	.200	#8	6	.97	.31	.27	.81
14RB-10FX	100	18-14	.200	#10	6	.97	.31	.27	.81
RB1157-200	1000	18-14	.200	#10	6	.97	.31	.27	.81
10RC-8FX	50	12-10	.250	#8	7	1.11	.38	.27	.90
RC1147-250	500	12-10	.250	#8	7	1.11	.38	.27	.90
10RC-10FX	50	12-10	.250	#10	7	1.11	.38	.27	.90
RC1157-250	500	12-10	.250	#10	7	1.11	.38	.27	.90
10RC-14FX	50	12-10	.250	1/4"	7	1.17	.50	.37	.90

U.L. Listed E9809. Installing tools: WT145C, WT2000, WT112M, ERG4001, ERG2003, WT2130A(RC)



Fork terminals allow easy installation since the mounting screw does not have to be completely removed. Catalogue numbers with the suffix X indicate an expanded insulation support. This means a wider wire entry to accommodate heavy wall insulation.

Stock thickness same as ring terminal of same size.

Most standard bulk catalogue numbers can be put on Mylar Tape for reel fed applications (i.e. 12050 tool and application dies). See pages 196-197. Please put the suffix M for Mylar Tape RA2573M. (Bulk number 1000 and 500 packages.)

Sta-Kon®

Terminals



These non-insulated fork terminals are made of electrolytic copper for high conductivity. They can be installed with crimping tools having a single indentor or double indentor (recommended for solid wire). Serrated barrel increase grip on wire. Wire range identification is stamped on the tongue of each terminal.

Stock thickness same as ring terminal of same size.

Most standard bulk catalogue numbers can be put on Mylar Tape for reel fed applications (i.e. 12050 tool and application dies). See pages 196-197. Please put the suffix M for Mylar Tape RA2573M. (Bulk number 1000 and 500 packages.)

Non-Insulated Fork

Cat. No.	Pkg. Qty.	Wire Range	Bolt Hole	Wt./lb. Per 1000	Dimensions			
					A	B	C	M
A18-6F	100	22-16	#6	4	.72	.25	.27	.59
A116	1000	22-16	#6	4	.72	.25	.27	.59
A18-8F	100	22-16	#8	4	.75	.31	.27	.59
A114	1000	22-16	#8	4	.75	.31	.27	.59
A18-10F	100	22-16	#10	4	.75	.31	.27	.59
A115	1000	22-16	#10	4	.75	.31	.27	.59
B14-6F	100	18-14	#6	6	.75	.31	.27	.59
B64	1000	18-14	#6	6	.75	.31	.27	.59
B19	1000	18-14	#6	6	.66	.25	.13	.50
B14-8F	100	18-14	#8	6	.75	.31	.27	.59
B65	1000	18-14	#8	6	.75	.31	.27	.59
B14-10F	100	18-14	#10	6	.75	.31	.27	.59
B115	1000	18-14	#10	6	.75	.31	.27	.59
B14-14F	100	18-14	1/4"	6	.90	.44	.38	.68
C10-6F	50	12-10	#6	7	.77	.31	.27	.63
C133	500	12-10	#6	7	.77	.31	.27	.63
C10-8F	50	12-10	#8	7	.82	.38	.27	.63
C114	500	12-10	#8	7	.82	.38	.27	.63
C10-10F	50	12-10	#10	7	.82	.38	.27	.63
C115	500	12-10	#10	7	.82	.38	.27	.63
C10-14F	50	12-10	1/4"	7	.98	.50	.37	.73
C116	500	12-10	1/4"	7	.98	.50	.37	.73

U.L. Listed E9809

Installing tools: WT111M, WT112M, WT110M, WT2000, ERG4002, ERG4005

