



These ring terminals are self-insulated with heat shrinkable polyolefin and internally coated sealant. Upon completed installation, a fully sealed connection is achieved to protect the joint against the degrading effects of galvanic action, corrosion, and environmental exposure.

RAS & RBS stock thickness: .03
RCS stock thickness: .04



Heat Shrinkable

These ring terminals, butt splices and disconnects are self-insulated with heat shrinkable polyolefin and internally coated sealant. Upon completed installation, a

fully sealed connection is achieved to protect the joint against the degrading effects of galvanic action, corrosion, and environmental exposure.




Heat Shrinkable Ring Terminals – Expanded Insulation Support

Cat. No.	Pkg. Qty.	Wire Range	Max. Ins.	Bolt Hole	Wt./lb. Per 1000	Dimensions			
						A	B	C	M
RAS18-6X	100	22-18	.170	#6	2	1.23	.25	.27	1.10
RAS18-8X	100	22-18	.170	#8	3	1.26	.31	.27	1.10
RAS18-10X	100	22-18	.170	#10	2	1.26	.31	.27	1.10
RBS14-6X	100	16-14	.200	#6	3	1.23	.25	.27	1.10
RBS14-8X	100	16-14	.200	#8	3	1.23	.25	.27	1.10
RBS14-10X	100	16-14	.200	#10	3-1/2	1.26	.31	.27	1.10
RCS10-6X	50	12-10	.250	#6	3	1.34	.31	.27	1.15
RCS10-8X	50	12-10	.250	#8	5	1.34	.37	.27	1.15
RCS10-10X	50	12-10	.250	#10	5	1.34	.37	.27	1.15
RCS10-14X	50	12-10	.250	1/4"	6	1.34	.49	.32	1.15

U.L. Listed E9809

Installing tool: WT1255

Note: Not available on Mylar Tape.




Heat Shrinkable Locking Fork Terminals – Expanded Insulation Support

Cat. No.	Pkg. Qty.	Wire Range	Max. Ins.	Bolt Hole	Wt./lb. Per 1000	Dimensions	
						A	B
RAS18-6FLX	100	22-18	.170	#6	5	1.350	.25
RAS18-8FLX	100	22-18	.170	#8	5	1.350	.29
RAS18-10FLX	100	22-18	.170	#10	5	1.350	.29
RBS14-6FLX	100	16-14	.200	#6	6	1.350	.25
RBS14-8FLX	100	16-14	.200	#8	6	1.350	.29
RBS14-10FLX	100	16-14	.200	#10	6	1.350	.29
RCS10-6FLX	50	12-10	.250	#6	8	1.350	.31
RCS10-8FLX	50	12-10	.250	#8	8	1.350	.37
RCS10-10FLX	50	12-10	.250	#10	8	1.350	.37
RCS10-14FLX	50	12-10	.250	1/4"	8	1.350	.49

U.L. Listed E9809

Installing tool: WT1255

Note: Heat Shrinkable terminals not available on Mylar Tape.






Heat Shrinkable-Fully Insulated 250 Disconnects – Female

Cat. No.	Pkg. Qty.	Wire Range	Max. Ins	Tab Size	Wt./lb. Per 1000	A
RAS18-250AX	25	22-18	.170	.250 x .032	4	1.82
RBS14-250AX	25	16-14	.200	.250 x .032	5	1.77
RCS10-250AX	50	12-10	.250	.250 x .032	6	1.80

Installing tool: WT1255



Heat Shrinkable-Fully Insulated 250 Disconnects – Male

Cat. No.	Pkg. Qty.	Wire Range	Max. Ins	Tab Size	Wt./lb. Per 1000	A
18RAS-251TX	25	22-18	.170	.250 x .032	4	1.80
14RBS-251TX	25	16-14	.200	.250 x .032	5	1.75
10RCS-251TX	25	12-10	.250	.250 x .032	6	1.80


Installing tool: WT1255



Heat Shrinkable Splices – Butt Type – Expanded Insulation

Cat. No.	Pkg. Qty.	Wire Range	Max. Ins	Wt./lb. Per 1000	A	B
2RAS18X	50	22-18	.170	3	1.50	.25
RAAS22X	1000	22-18	.170	3	1.50	.25
2RBS14X	50	16-14	.200	3	1.50	.26
RBBS22X	500	16-14	.200	3	1.50	.26
2RCS10X	25	12-10	.250	7	1.60	.31
RCCS22X	500	12-10	.250	7	1.60	.31

Installing tool: WT1255



These butt splices are self-insulated with heat shrinkable polyolefin and internally coated sealant. Upon completed installation, a fully sealed connection is achieved to protect the joint against the degrading effects of galvanic action, corrosion, and environmental exposure.



WT-PTORCH

Cat. No.	Description
WT-PTORCH	Hand-Held Butane Torch (Butane not supplied)