



Harnessing Accessories




1/8" max
Snap-in 1/4" hole

Mechanical-Locking Routing Clamps

Bulk Cat. No.	Mounting Hole Size	Maximum Wire Bundle Diameter (in.)	Width (in.)	Length (in.)	Bulk Pkg.
TC88	.250	.500	.250	.891	100
TC95	.250	1.000	.500	1.590	100

The locking clamp is available in several mounting styles, as shown. This clamp acts as a retainer during wire routing and as a positive clamp when desired. Anti-rotational peg is available.




Here is an inexpensive harness clip for grouping wires in appliances, office equipment and other noncritical applications.

Designed to perform the same basic function as a cable tie in holding wires together, the new adjustable, self-locking clip requires no tools for installation. A projecting prong is simply pressed into a 1/4" hole where it compresses and locks. The simple ratchet-type lock is released by moving the locking lever.

Harness Clips

Bulk Cat. No.	Mounting Hole Size	Maximum Wire Bundle Diameter (in.)	Bulk Pkg.
HCP438	1/4	.375	1000








AC-loop retaining clamp is ideal to support long runs in point-to-point wiring or as a harness aid. Rigid PVC.

HBundle-Retaining Clamp

Bulk Cat. No.	Mounting Method	Maximum Wire Bundle Diameter (in.)	Width (in.)	Bulk Pkg.
TC70	#10 screw	.250	.400	100
TC71	#10 screw	.500	.400	100
TC72	#10 screw	.750	.500	100
TC73	#10 screw	1.000	.500	100
TC74	#10 screw	1.500	.500	100

Harnessing Accessories



Wire-Bundle Retainers

Bulk Cat. No.	Fastener	Maximum Wire Bundle Diameter (in.)	Width (in.)	Height (in.)	Bulk Pkg.
TC86	#6 screws	.750	1.750	1.813	25
TC87	#6 screws	1.250	2.469	2.281	10

These retainers consist of a spring-loaded clip and an elastic bundle support. Wires are inserted simply by snapping them through spring-loaded clips. Wires are held 1/4 inch above work surface for easy tying.

Harness-Board Nails

Bulk Cat. No.	A (in.)	Dimensions B (in.)	C (in.)	Bulk Pkg.
HBP34	.750	.625	.072	100
HBP-1	1.000	.625	.072	100
HBP112	1.500	.625	.082	100
HBP2	2.000	.625	.092	100
HBP212	2.500	.625	.105	100
HBP3	3.000	.625	.120	100

Hardened, nickel plated steel.



Bulkhead Bundle Support Feed-Through

Bulk Cat. No.	Mounting Method	Maximum Tie Width Accom.	Width (in.)	Length (in.)	Bulk Pkg.
TC131	#6 screw	.190	1.115	1.890	1000

TC131 bulkhead mounting base can be installed from either side. Ties are installed through the clamp on either side of the bulkhead.

Wire-Bundle Spacer

Cat. No.	Maximum Tie Width Accom.	Width (in.)	Length (in.)	Std. Pkg.	Bulk Pkg.
TC5339	.190	.266	.500	100	500