

## DuraGard waterproof connections

30 A standard service and 30 A reverse service



### Device ratings and polarizations

Pole	Wire	Safety polarization (receptacle)	Voltage	Cat. no. ▼ <input type="checkbox"/>	Cat. no. ▼ <input type="checkbox"/>
Product type				Male plug	Female connector
2	3		125 V AC	9P33U1	9C33U1
2	3		250 V AC	9P33U2	9C33U2
2	3		277 V AC	9P33U3	9C33U3
2	3		480 V AC	9P33U4	9C33U4
2	3		600 V AC	9P33U5	9C33U5
2	3		through 600 V AC/250 V DC	9P33U0	9C33U0
3	4		125/250 V AC	9P34U1	9C34U1
3	4		3Ø 250 V AC	9P34U2	9C34U2
3	4		3Ø 480 V AC	9P34U4	9C34U4
3	4		3Ø 600 V AC	9P34U5	9C34U5
3	4		through 600 V AC/250 V DC	9P34U0	9C34U0

Maximum 600 V AC/250 V DC

Add suffix - / xxxx for bushing I.D. (page 64) or conduit adapter assembled.

◆ "W" suffix indicates watertight receptacle; "F" suffix indicates splash-proof spring flap cover included.

\* Consult Technical Services.



Pole	Wire	Standard bushing I.D.: Plug/conn.*	<input type="checkbox"/> Cat. no. ▼ Female receptacle	<input type="checkbox"/> Cat. no. ▼ Female plug (reverse service)	<input type="checkbox"/> Cat. no. ▼ Male receptacle (reverse service)
Product type					
2	3	Standard 0.700"; for optional size, see page 64	9R33U1W	9F33U1	9B33U1F
2	3		9R33U2W	9F33U2	9B33U2F
2	3		9R33U3W	9F33U3	9B33U3F
2	3		9R33U4W	9F33U4	9B33U4F
2	3		9R33U5W	9F33U5	9B33U5F
2	3		9R33U0W	9F33UØ	9B33UØF
3	4	Standard 0.750"; for optional size, see page 64	9R34U1W	9F34U1	9B34U1F
3	4		9R34U2W	9F34U2	9B34U2F
3	4		9R34U4W	9F34U4	9B34U4F
3	4		9R34U5W	9F34U5	9B34U5F
3	4		9R34U0W	9F34UØ	9B34UØF

Add suffix - / xxx for bushing I.D. (page 64) or conduit adapter assembled.  
 ♦ "W" suffix indicates watertight receptacle; "F" suffix indicates splash-proof spring flap cover included.  
 \* Consult Technical Services.