

NPG Quick-Connect™ cable gland

Fast and simple




Speed and ease of installation make the NPG Quick-Connect cable gland the ideal choice for panel builders and volume installers, as the ease of installation comes with no reduction in performance.

Features and benefits

- Ideal for panel builders, OEMs and volume installers
- Single piece design that requires no additional parts (no locknut required)
- Low internal profile
- Suitable for use with unarmoured cable, portable cord and tray cable
- Halogen-free nylon (PA6) available in black, grey and light grey
- IP66 - IP68 (5 bar 30 mins) rating
- Corrosion resistant
- No locknut required
- Another innovative solution for cable protection systems



Diagrams



NPT – NPG Quick-Connect

Listing	Cat. no.	Trade size (in.)	Cable range mm (in.)		Hole size mm (in.)		Nominal dimension mm (in.)				
			Min.	Max.	Min.	Max.	A	B	C	W1	W2
cUL US	NPG-0381x	3/8	5.0 (0.197)	10.0 (0.394)	17.65 (0.695)	18.85 (0.742)	10.0 (0.394)	41.2 (1.622)	26.5 (1.043)	22.0 (0.866)	22.0 (0.866)
	NPG-0501x	1/2	6.0 (0.236)	12.0 (0.472)	21.84 (0.860)	23.01 (0.906)	10.0 (0.394)	39.2 (1.543)	30.5 (1.201)	24.0 (0.945)	24.0 (0.945)
cUL US	NPG-0502x	1/2	10.0 (0.394)	14.0 (0.551)	21.84 (0.860)	23.01 (0.906)	10.0 (0.394)	39.8 (1.567)	30.5 (1.201)	27.0 (1.063)	27.0 (1.063)
	NPG-0751x	3/4	13.0 (0.512)	18.0 (0.709)	27.78 (1.094)	28.98 (1.141)	10.0 (0.394)	41.9 (1.650)	39.0 (1.535)	33.0 (1.299)	33.0 (1.299)
	NPG-1001x	1	18.0 (0.709)	25.0 (0.984)	34.51 (1.359)	35.71 (1.406)	10.0 (0.394)	50.1 (1.972)	47.5 (1.870)	42.0 (1.654)	42.0 (1.654)

Also available in Metric sizes from M16 to M32.
 Replace the “x” of the catalogue number by one of the following:
 B = black (RAL 9005), G = grey (RAL 7001), LG = light grey (RAL 7035)
 Note: Product must be installed in accordance with applicable national and local electrical codes.

- 01 Snap
- 02 Insert cable
- 03 Tighten

Quick-install cable gland

Thanks to its built-in nylon locking mechanism, the NPG Quick-Connect cable gland offers an easy, three-step installation: Simply snap the gland into a

properly sized knockout until it clicks, insert the cable and tighten. No locknuts or separate parts are required.



See our installation video at tnb.ca/npg



01



02




03

- 04
- NPG-038-RT (3/8")
- NPG-050-RT (1/2")
- NPG-075-RT (3/4")
- NPT-100-RT (1")

Removal tool

- One removal tool included with each inner packaging
- Also sold separately (light grey plastic - RAL 7035)
- Push from inside the enclosure using this tool to easily remove the cable gland.



04

ABB Installation Products Ltd.
 Electrification business
 700 Thomas Avenue
 Saint-Jean-sur-Richelieu, Quebec J2X 2M9
 Tel.: +1 (450) 347 5318
 Toll Free: +1 (800) 362 2952
 Fax: +1 (450) 347 1976

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB Inc. does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its contents – in whole or in parts – is forbidden without prior written consent of ABB Inc..
 Copyright © 2019 ABB
 All rights reserved