


PL17 Series

100 A 600 V; polyphase

Product specifications

- Conductor range: 6–1/0 AWG
- Aluminum tunnel type connectors for both load and line sides
- For overhead, underground and combination overhead/underground

- Supplied with screw type ring
- Weatherproof Type 3R enclosure



Cat. no.	Description	Dimensions (in.)			Weight each	
		H	W	D	lb	kg
7 Jaw						
PL17-INV	Overhead, hub opening	15 ⁵ / ₈	8 ³ / ₁₆	5 ⁷ / ₁₆	12	5.4
PL17-INV-HQ	Overhead, hub opening (Hydro-Québec approved)	15 ⁵ / ₈	8 ³ / ₁₆	5 ⁷ / ₁₆	12	5.4
PL17-INTV-HQ	Underground (Hydro-Québec spec)	15 ⁵ / ₈	8 ³ / ₁₆	5 ⁷ / ₁₆	12	5.4
PL17-INTCV	Combination overhead-underground	15 ⁵ / ₈	8 ³ / ₁₆	5 ⁷ / ₁₆	12	5.4
PL17-INTCV-HQ	Combination overhead-underground (Hydro-Québec approved)	15 ⁵ / ₈	8 ³ / ₁₆	5 ⁷ / ₁₆	12	5.4
PL17-V	Overhead, hub opening	15 ⁵ / ₈	8 ³ / ₁₆	5 ⁷ / ₁₆	12	5.4
PL17-TV	Underground	15 ⁵ / ₈	8 ³ / ₁₆	5 ⁷ / ₁₆	12	5.4
PL17-TCV	Combination overhead-underground	15 ⁵ / ₈	8 ³ / ₁₆	5 ⁷ / ₁₆	12	5.4
Factory-installed accessories						
Include: -IN					Insulated neutral	



Diagrams

