Red Dot Weatherproof metallic boxes

Round boxes, extensions and covers



Applications:

- Junction for branch conduits
- Spacious, accessible wiring chamber provides a convenient location to maintain or change a system, pull conductors and make splices

Features/benefits:

- Copper-free* aluminum provides increased corrosion resistance
- Precision-cast and machined surfaces permit safer wire pulling
- · Clean cover edges provide good gasket sealing
- Precision NPT threads enable trouble-free field installation for rigid conduit or EMT fitting
- Deep-slotted zinc plated steel cover screws for faster installation
- Clear UL, CSA and cubic content markings speed approval by inspectors

Standard materials:

- Boxes: Die-cast aluminum alloy
- · Cover: Stamped aluminum
- Gaskets: Composition

Standard finish:

· Powder-coated finish

Compliances:

- · UL listed and CSA certified
- * Less than 0.004% copper content.





SE-48

Boxes

Cat. no.	Colour	Hub size (in.)	Description	Std. ctn.
Five outlets, 41/8" diar	neter			
S-47	Grey	1/2	5 Outlets, cast	36
S110CN	Grey	1/2	5 Outlets with ground screw	16
S110BKCN	Black	1/2	5 Outlets with ground screw	16
S110BRCN	Bronze	1/2	5 Outlets with ground screw	16
S110WHCN	White	1/2	5 Outlets with ground screw	16
S-48	Grey	3/4	Mounting lugs, 4 closure plugs	36
S48CFB	Grey	3/4	Ceiling fan box and cover rated for 50 lb fixture or 35 lb fan	10
D-PAK				
DS-47-BR	Bronze	1/2	5 Outlets	8
DS-47-WH	White	1/2	5 Outlets	8
DS-47B	Grey	1/2	With blank cover	8
DS-48B	Grey	3/4	With blank cover	8

Note: Boxes are raintight when used with appropriate Red Dot covers.

4⅓" Round extensions



Cat. no.	Colour	Hub size (in.)	Description	Std. ctn.
Four outlets, 41/8" dia	meter, 1%" deep	·		
S130E-CN	Grey	1/2	4 Outlets	8
SE-48	Grey	3/4	4 Closure plugs, gasket and screws	5

Iberville and Red Dot Weatherproof metallic boxes

Round boxes, extensions and covers





CIC-8444 / CIC-8448

	Hub	size (in.)	No. of	No. of		Α	В	С	D	Volume
Cat. no.		Bottom	lugs	plugs	Description	(in.)	(in.)	(in.)	(in.)	(cu. in.)
Weatherpre	oof jund	tion box l	cits (ca	st alumi	num)					
CIC-8444	4 x ½	1/2	2	4 x ½	Includes cover, gasket, plugs and mounting screws	15/8	315/16	5	45/16	17.3
CIC-8446	4 x ¾	1/2	2	3 x ³ / ₄	Includes cover, gasket, plugs and mounting screws	1 ½	315/16	5	45/16	17.3
	4 x 3/4	1/2	2	1 x ½	Includes cover, gasket, plugs and mounting screws	1 ½	315/16	5	45/16	17.3
CIC-8448	4 x 1	1/2	2	3 x 1	Includes cover, gasket, plugs and mounting screws	1 ½	315/16	5	45/16	17.3
	4 x 1	1/2	2	1 x ½	Includes cover, gasket, plugs and mounting screws	1 ½	315/16	5	45/16	17.3
Outlet box	4½ dia.	(cast alun	ninum)							



CIC-8495





 $- 1\frac{1}{2} 3\frac{15}{16} 4\frac{5}{8} 4\frac{5}{16}$




17.3



SS-B

CCRSB

— Round blank covers



	_		Std.
Cat. no.	Colour	Description	ctn.
4½" Diame	eter		
SS-B	Grey	Weatherproof cover with gasket and screws	15
5" Diamet	er		
CCRSB	CCRSB White Mounting holes 2¾" on center (not raintight)		50
CCRB	White	Mounting holes 3½" on center (not raintight)	50

Note: Covers are raintight when used with appropriate Red Dot boxes. All covers packed with gasket and screws.



CIC-93 / S341E-R

Round blank covers



Cat. no.	Description
Weatherproof ro	und cover – 4¾6 in. dia. (stamped aluminum)
CIC-93	For 4 in. weatherproof round box; includes gasket and mounting screws
S341E-R*	Round blank weatherproof box cover, colour grey
*cULus	



S621E

Round gasket

Cat. no.	Colour	Description	Std. ctn.
S621E	Black	Round gasket	50



PLG-1-RD / PLG-2-RD / PLG-3-RD

Close-up plugs (zinc)

olugs (zinc)			OF C
	Colour	Size (in.)	Descrip

Cat. no.	Colour	Size (in.)	Description
PLG-1-RD	Grey	1/2	Close-up plugs
PLG-2-RD	Grey	3/4	Close-up plugs
PLG-3-RD	Grey	1	Close-up plugs



S603E-R

Nonmetallic plugs

	c UL us
gs	CQLJUS

			_
Cat. no.	Colour	Size (in.)	Description
S603E-R	Grey	1/2	Close-up plugs bag/4
S603BRE-R	Bronze	1/2	Close-up plugs bag/4
S603WHE-R	White	1/2	Close-up plugs bag/4
S603ASSTD-R	Assorted	1/2	Close-up plugs bag/8

