

## Medium-voltage cable accessories technical information

Table W

Table W

Applicable cat. no. use for following products	Cable insulation diameter in inches		Symbol for W	Applicable cat. no. use for following products	Cable insulation diameter in inches		Symbol for W
	Min.	Max.			Min.	Max.	
<b>Table W1</b>				<b>Table W7</b>			
151SP/SR	0.575	0.740	A	K656I/CY/CH	0.420	0.660	D
151LS/LY	0.635	0.905	B	K655/656LR	0.530	0.680	E
161DLR				K655/656SR			
161/162LR	0.805	1.060	C	655/656LINK	0.640	0.820	F
161/162LRJS	0.890	1.220	D	K655/656LINK	0.760	0.950	G
161LR/161LRJS	1.090	1.310	E	655/656ETP	0.850	1.050	H
261LR/261LRJS				K655/656ETP	0.980	1.180	J
162LR/162LRJS				655/656RTP	1.090	1.310	K
261DLR				K655/656LRTP	1.180	1.465	L
262LR/262LRJS				655/656BI-LINK	1.280	1.430	LM
					1.370	1.630	M
					1.550	1.780	N
					1.665	1.785	PA
					1.725	1.935	P
<b>Table W2</b>				<b>Table W8</b>			
273RLR	0.760	0.950	G	15PCJ-1	0.640	0.820	F
274RLR	0.850	1.050	H	15PCJ-2	0.760	0.950	G
273DLR	0.980	1.180	J		0.850	1.050	H
	1.090	1.310	K		0.980	1.180	J
					1.090	1.310	K
					1.180	1.465	L
					1.280	1.430	LM
					1.370	1.630	M
					1.515	1.780	N
					1.725	1.935	P
					1.900	2.120	Q
<b>Table W3</b>				<b>Table W9</b>			
375LR	0.850	1.050	H	25PCJ-1	0.760	0.950	G
376LR	0.980	1.180	J	25PCJ-2	0.850	1.050	H
	1.090	1.310	K	755/756LR	0.980	1.180	J
	1.235	1.465	L	755/756LINK	1.090	1.310	K
				755/756ETP	1.090	1.310	K
				755/756LRTP	1.180	1.465	L
				755/756BI-LINK	1.370	1.630	M
				755CA/CK/TCK	1.515	1.780	N
					1.725	1.935	P
					1.900	2.120	Q
					2.115	2.235	R
<b>Table W4</b>							
167/168RLR	0.640	0.820	F				
167LRT	0.760	0.950	G				
	0.850	1.050	H				
	0.980	1.180	J				
	1.090	1.310	K				
<b>Table W5</b>							
167/168ELR	0.665	0.895	6689				
273/274DEL	0.740	0.950	7495				
273/274ELR	0.880	1.100	88110				
167/168DEL	1.090	1.310	K				
<b>Table W6</b>							
10EP	0.495	0.585	EB				
152EA	0.525	0.635	EF				
160CA*	0.575	0.685	FA				
(*EB-FA only)	0.625	0.735	FAB				
	0.675	0.785	FB				
	0.725	0.835	FG				
	0.775	0.885	GA				
	0.825	0.935	GAB				
	0.875	0.985	GB				

## Medium-voltage cable accessories technical information

### Table W & Table X

Table W (continued)

Applicable cat. no. use for following products	Conductor size AWG or kcmil	Symbol for W		Applicable cat. no. use for following products	Conductor size AWG or kcmil	Symbol for W	
		Strand./ compr.	Compt./ solid.			Strand./ compr.	Compt./ solid.
<b>Table W10</b>				<b>Table W16</b>			
35PCJ-1	0.850	1.050	H	252LR	0.575	0.740	A
35PCJ-2	0.980	1.180	J	252LRJS	0.635	0.905	B
	1.090	1.310	K		0.805	1.060	C
	1.180	1.465	L		0.890	1.220	D
	1.370	1.630	M		1.090	1.310	E
	1.515	1.780	N				
	1.725	1.935	P				
	1.900	2.120	Q				

Table X

Applicable cat. no. use for following products	Conductor size AWG or kcmil	Symbol for X		Applicable cat. no. use for following products	Conductor size AWG or kcmil	Symbol for X	
		Strand./ compr.	Compt./ solid.			Strand./ compr.	Compt./ solid.
<b>Table X1</b>				<b>Table X6</b>			
167/168ELR/DELRL	#2	210	220	K655/656ETP	650	750/800	360
273/274ELR/DELRL	#1	220	230	755/756ETP	700/750	900	380
156LR, 161/162LR	1/0	230	240	655/656BI-LINK	800	-	390
261/262LR,167LRT	2/0	240	250	K655/656BI-LINK	900	1,000	400
167/168RLR,167DLR	3/0	250	260	755BI-LINK	1,000	-	410
273/274RLR,273DLR	4/0	260	270	655CK, 755CK	-	1,250	420
00400, 02500, 02509, 02702, 02800, K151SP/SR,	250	270	-	655TCK, 03600	-	-	440
375LR/376LR				03602, 03700, 03702	1250	-	440
<b>Table X2</b>				<b>Table X7</b>			
375/376LR	1/0	230	240	15PCJ1	#2	220	210
375/376LR	2/0	240	250	25PCJ1	#1	230	220
	3/0	250	260	35PCJ1	1/0	240	230
	4/0	260	270	15PCJ2	2/0	250	240
<b>Table X6</b>				<b>Table X9</b>			
655/656LRTP	-	#2	210	25PCJ2	2/0	250	240
K655/656LRTP	#2	#1	220	35PCJ2	3/0	260	250
755/756LRTP	#1	1/0	230		4/0	270	260
K656I/Y/H, K655/656LR	1/0	2/0	240		250	280	270
755/756LR, K655/656SR	2/0	3/0	250		350	300	290
655/656LINK, K655/656LINK	3/0	4/0	260		500	330	310
755/756LINK, 655/656ETP	4/0	250	270		750	380	360
K655/656ETP, 755/756ETP	250	300	280		1,000	410	400
655/656BI-LINK	300	350	290		1,250	440	420
K655/656BI-LINK	350	400	300	<b>Table X9</b>			
755BI-LINK, 655CK	400	450	310	PCT1	#2	220	210
755CK, 655TCK, 03600, 03602, 03700, 03702	450	500/550	320	PCT2	#1	230	220
K655/656LRTP	500	600	330	01000	1/0	240	230
755/756LRTP, K656I/Y/H	550	650	340	01010	2/0	250	240
K655/656LR, K655/656LR	600	700	350		3/0	260	250
755/756LR, K655/656SR	600	700	350		4/0	270	260
655/656LINK, K655/656LINK							
755/756LINK, 655/656ETP							
K655/656ETP, 755/756ETP							