

Type: _____
 Project/Location: _____
 Contractor: _____
 Prepared By: _____
 Date: _____
 Model No.: _____

EA Triangular Series

Extruded Aluminum
Pictogram Exit Sign



FEATURES

- Long-life white LED light sources is warranted for ten (10) years
- Supplied standard with two pictogram films, for direction selection
- Universal AC input: two-wire 120 to 347VAC; standard DC input: two-wire 6 to 24VDC
- Energy efficient – consumes less than 2.5W in AC or DC-remote mode per face
- Easy access to wiring entry for all mounting options
- Meets or exceeds CSA 22.2 No.141-15
 See warranty details at: www.tnb.ca/en/brands/emergi-lite

TYPICAL SPECIFICATIONS

Supply and install the **Emergi-Lite® EA Triangular Series** pictogram Exit Signs.

The equipment shall operate with universal 2-wire AC input voltage of 120 to 347VAC at less than 2.5W and universal 2-wire DC input voltage from 6 to 24VDC at less than 1.5W per face. The equipment shall be suitable for wall or pendant, or ceiling mount. The housing shall be constructed of rugged extruded aluminum. The faceplate(s) shall be constructed of extruded aluminum and shall incorporate a protective clear polycarbonate panel. Each face plate shall come standard with two legend films for pictogram and direction selection.

The light source shall be white light-emitting diodes (LED) and shall provide even illumination in normal and emergency operation.

The pictogram Exit Sign shall meet CSA 22.2 No.141-15.


The equipment shall be **Emergi-Lite®** Model: _____.



Made in Canada

DIMENSIONS

Dimensions are approximate and subject to change.



POWER CONSUMPTION (per face)

MODEL	AC SPECS		DC SPECS	
AC/DC standard	120 to 347VAC	Less than 2.5W	6 to 24VDC	Less than 1.5W

ORDERING INFORMATION

SERIES	FACES / MOUNTING	COLOURS	VOLTAGE	OPTIONS
EA = pictogram exit sign	T2S = triangular 2 sided, wall and pendant mount only T3S = triangular 3 sided, pendant mount only	W = factory white	UNIV = 120 to 347VAC; 6 to 24VDC	TP = tamper-proof screws *990.0119-E = tamper-proof bit (sold separately)

EXAMPLE: EAT2SWUNIVTP